

ARC-HKIVB14



2MP 1080pTVI Bullet Cam 5-50 Motorized Zoom Lens Dual Volt

Description

CCTV Cameras : ARC-HKIVB14

Model		ARC-HKIVB14
Parameters	2MP CMOS Motorized Vari-focal IR Bullet Camera	
Camera		
Image Sensor	2.0Mega Progressive Scan CMOS	
Signal System	PAL/NTSC	
Effective Pixels	1956(H)×1266(V)	
Min. illumination	0.01Lux @ (F1.2,AGC ON),0 Lux with IR	
Shutter Time	1/25(1/30)sec~ 1/50,000sec	
Lens Mount	5-50mm motorized VF lens	
Day & Night	ICR	
Angle Adjustment	Pan: 0°~360°; Tilt:0°~ 90°; Rotate: 0°~360°	
Synchronization	Internal synchronization	
WDR	120dB	
Video Frame Rate	1080P@25/30fps	
HD Video Output	1 turbo HD output	
CVBS Output	1Vp-p Composite Output(75Ω/BNC)	
S/N Ratio	>62dB	
Menu		
Camera ID	On/off (15 characters, position programmable)	
AGC	Support	
D/N Mode	Color/BW/EXT	
White Balance	ATW/ AWC-SET/ Manual	
Privacy Mask	On/Off, maximum 8 zones	
Motion Detection	On/Off, maximum 4 zones	
BLC	Support	
Anti-flicker	On/off	
Language	Chinese/ English	
White Balance	Eclipse, Digital noise reduction, Digital zoom(62x), Slow shutter, Mirror, Defog, Defect pixel correction, SMART D-ZOOM	
Scene	Indoor/ Outdoor/ Indoor1/ LOW-LIGHT	
General		
Working Temperature/Humidity	-40 °C – 60 °C (-40 °F – 140 °F) Humidity 90% or less (non-condensing)	
Power Supply	AC24V±15%/ DC12V±15% Dual	
Power Consumption	Max. 11W(heater off) Max. 20W(heater on)	
Weather Proof Ratings	IP67	
IR Range	100-110m	
Communication	Pelco-C protocol,HIKVISION-C protocol CVBS output: Pelco-C(need UTC controller)	
Dimensions	313.5*100.8*107.3	
Weight(approx.)	1700g	